

Package: rocker (via r-universe)

September 8, 2024

Title Database Interface Class

Version 0.3.1

Description 'R6' class interface for handling relational database connections using 'DBI' package as backend. The class allows handling of connections to e.g. PostgreSQL, MariaDB and SQLite. The purpose is having an intuitive object allowing straightforward handling of SQL databases.

License MIT + file LICENSE

URL <https://github.com/nikolaus77/rocker>

BugReports <https://github.com/nikolaus77/rocker/issues>

Encoding UTF-8

Imports DBI, R6, sodium

Suggests covr, crayon, knitr, RMariaDB, testthat (>= 3.0.0), rmarkdown, RPostgres, RSQLite

RoxygenNote 7.2.1

VignetteBuilder knitr

Config/testthat/edition 3

Repository <https://nikolaus77.r-universe.dev>

RemoteUrl <https://github.com/nikolaus77/rocker>

RemoteRef HEAD

RemoteSha 0655c90cf0a5bd3ad2e61627fc80efc5089178f7

Contents

appendTable	2
begin	3
canConnect	4
clearResult	5
columnInfo	6
commit	7

connect	8
createTable	9
disconnect	10
execute	11
existsTable	12
fetch	13
getInfoCon	14
getInfoDrv	15
getInfoRes	16
getQuery	17
getRowCount	18
getRowsAffected	19
getStatement	20
hasCompleted	21
isValidCon	22
isValidDrv	23
isValidRes	24
listFields	25
listObjects	26
listTables	27
newDB	28
readTable	28
removeTable	29
rocker-R6-class	30
rocker-README	56
rocker-S3-functions	78
rollback	79
sendQuery	80
sendStatement	81
setupDriver	82
setupMariaDB	83
setupPostgreSQL	84
setupSQLite	85
unloadDriver	86
validateCon	87
writeTable	88

Index	89
--------------	-----------

appendTable	<i>Append data to table.</i>
-------------	------------------------------

Description

Append data to table.

Usage

```
appendTable(db, name, value, ...)
```

Arguments

db	rocker object
name	Table name
value	Values data.frame
...	Optional, additional suitable parameters passed to <code>DBI::dbAppendTable()</code>

Value

Number of appended rows invisibly

See Also

Other rocker-S3-functions: [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::createTable(db, "mtcars", mtcars)
rocker::appendTable(db, "mtcars", mtcars)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

```
begin
```

```
Begin transaction.
```

Description

Begin transaction.

Usage

```
begin(db, ...)
```

Arguments

db rocker object
 ... Optional, additional suitable parameters passed to `DBI::dbBegin()`

Value

Invisible self

See Also

Other rocker-S3-functions: `appendTable()`, `canConnect()`, `clearResult()`, `columnInfo()`, `commit()`, `connect()`, `createTable()`, `disconnect()`, `execute()`, `existsTable()`, `fetch()`, `getInfoCon()`, `getInfoDrv()`, `getInfoRes()`, `getQuery()`, `getRowCount()`, `getRowsAffected()`, `getStatement()`, `hasCompleted()`, `isValidCon()`, `isValidDrv()`, `isValidRes()`, `listFields()`, `listObjects()`, `listTables()`, `readTable()`, `removeTable()`, `rocker-README`, `rocker-S3-functions`, `rocker-package`, `rollback()`, `sendQuery()`, `sendStatement()`, `setupDriver()`, `setupMariaDB()`, `setupPostgreSQL()`, `setupSQLite()`, `unloadDriver()`, `validateCon()`, `writeTable()`

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::begin(db)
rocker::sendStatement(db, "DELETE FROM mtcars WHERE gear = 3;")
rocker::clearResult(db)
rocker::commit(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

canConnect

Test connection parameters.

Description

Test connection parameters.

Usage

```
canConnect(db, ...)
```

Arguments

db rocker object
 ... Optional, suitable parameters passed to `DBI::dbCanConnect()`

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::canConnect(db)
rocker::unloadDriver(db)
```

clearResult

Clear query or statement result.

Description

Clear query or statement result.

Usage

```
clearResult(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbClearResult()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```

db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
output <- rocker::fetch(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)

```

columnInfo

*Information on query result columns.***Description**

Information on query result columns.

Usage

```
columnInfo(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbColumnInfo()

Value

Information table

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```

db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")

```

```

rocker::columnInfo(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)

```

commit

Commit transaction.

Description

Commit transaction.

Usage

```
commit(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbCommit()

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```

db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::begin(db)
rocker::sendStatement(db, "DELETE FROM mtcars WHERE gear = 3;")
rocker::clearResult(db)
rocker::commit(db)
rocker::disconnect(db)
rocker::unloadDriver(db)

```

connect	<i>Establish database connection using stored parameters.</i>
---------	---

Description

Establish database connection using stored parameters.

Usage

```
connect(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbConnect()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

createTable	<i>Create empty formatted table.</i>
-------------	--------------------------------------

Description

Create empty formatted table.

Usage

```
createTable(db, name, fields, ...)
```

Arguments

db	rocker object
name	Table name
fields	Template data.frame
...	Optional, additional suitable parameters passed to DBI::dbCreateTable()

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::createTable(db, "mtcars", mtcars)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

disconnect	<i>Disconnect database.</i>
------------	-----------------------------

Description

Disconnect database.

Usage

```
disconnect(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbDisconnect()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

execute	<i>Execute SQL statement in database. Combination of functions <code>execute</code> and <code>clearResult</code>. If required, database is automatically connected and disconnected.</i>
---------	--

Description

Execute SQL statement in database. Combination of functions `execute` and `clearResult`. If required, database is automatically connected and disconnected.

Usage

```
execute(db, statement, ...)
```

Arguments

db	rocker object
statement	SQL statement (UPDATE, DELETE, INSERT INTO, ...)
...	Optional, additional suitable parameters passed to DBI::dbSendStatement()

Value

Number of affected rows

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::execute(db, "DELETE FROM mtcars WHERE gear = 3;")
rocker::disconnect(db)
rocker::unloadDriver(db)
```

existsTable	<i>Check if table exists.</i>
-------------	-------------------------------

Description

Check if table exists.

Usage

```
existsTable(db, name, ...)
```

Arguments

db	rocker object
name	Table name
...	Optional, additional suitable parameters passed to <code>DBI::dbExistsTable()</code>

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::existsTable(db, "mtcars")
rocker::disconnect(db)
rocker::unloadDriver(db)
```

fetch	<i>Fetch SQL query result from database.</i>
-------	--

Description

Fetch SQL query result from database.

Usage

```
fetch(db, n = -1, ...)
```

Arguments

db	rocker object
n	Number of record to be fetched
...	Optional, additional suitable parameters passed to DBI::dbFetch()

Value

Records

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
output <- rocker::fetch(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

getInfoCon	<i>Information on connection object.</i>
------------	--

Description

Information on connection object.

Usage

```
getInfoCon(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbGetInfo()</code>

Value

Information list

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::getInfoCon(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

getInfoDrv	<i>Information on driver object.</i>
------------	--------------------------------------

Description

Information on driver object.

Usage

```
getInfoDrv(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbGetInfo()

Value

Information list

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::getInfoDrv(db)
rocker::unloadDriver(db)
```

getInfoRes	<i>Information on result object.</i>
------------	--------------------------------------

Description

Information on result object.

Usage

```
getInfoRes(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbGetInfo()

Value

Information list

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
rocker::getInfoRes(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

getQuery	<i>Retrieve SQL query from database. Combination of functions sendQuery(), fetch() and clearResult(). If required, database is automatically connected and disconnected.</i>
----------	--

Description

Retrieve SQL query from database. Combination of functions sendQuery(), fetch() and clearResult(). If required, database is automatically connected and disconnected.

Usage

```
getQuery(db, statement, n = -1, ...)
```

Arguments

db	rocker object
statement	SQL query (SELECT)
n	Number of record to be fetched at once. All records will be fetched.
...	Optional, additional suitable parameters passed to <code>DBI::dbSendQuery()</code>

Value

Records

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
output <- rocker::getQuery(db, "SELECT * FROM mtcars;")
rocker::disconnect(db)
rocker::unloadDriver(db)
```

getRowCount	<i>Information on number of retrieved rows.</i>
-------------	---

Description

Information on number of retrieved rows.

Usage

```
getRowCount(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbGetRowCount()</code>

Value

Number of retrieved rows

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
output <- rocker::fetch(db)
rocker::getRowCount(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

getRowsAffected	<i>Information on number of affected rows.</i>
-----------------	--

Description

Information on number of affected rows.

Usage

```
getRowsAffected(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbGetRowsAffected()

Value

Number of affected rows

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendStatement(db, "DELETE FROM mtcars WHERE gear = 3;")
rocker::getRowsAffected(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

getStatement	<i>Information on sent statement.</i>
--------------	---------------------------------------

Description

Information on sent statement.

Usage

```
getStatement(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbGetStatement()

Value

Statement text

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
rocker::getStatement(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

hasCompleted	<i>Information whether all records were retrieved.</i>
--------------	--

Description

Information whether all records were retrieved.

Usage

```
hasCompleted(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbHasCompleted()

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
output <- rocker::fetch(db, 5)
rocker::hasCompleted(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

isValidCon	<i>Check connection object.</i>
------------	---------------------------------

Description

Check connection object.

Usage

```
isValidCon(db, onLostNull = FALSE, ...)
```

Arguments

db	rocker object
onLostNull	TRUE or FALSE. If connection lost, set .con to NULL
...	Optional, additional suitable parameters passed to <code>DBI::dbIsValid()</code>

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::isValidCon(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

isValidDrv	<i>Check driver object.</i>
------------	-----------------------------

Description

Check driver object.

Usage

```
isValidDrv(db, onLostNull = FALSE, ...)
```

Arguments

db	rocker object
onLostNull	TRUE or FALSE. If driver lost, set .drv to NULL
...	Optional, additional suitable parameters passed to DBI::dbIsValid()

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::isValidDrv(db)
rocker::unloadDriver(db)
```

isValidRes	<i>Check result object.</i>
------------	-----------------------------

Description

Check result object.

Usage

```
isValidRes(db, onLostNull = FALSE, ...)
```

Arguments

db	rocker object
onLostNull	TRUE or FALSE. If result lost, set .res to NULL
...	Optional, additional suitable parameters passed to DBI::dbIsValid()

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
rocker::isValidRes(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

listFields	<i>List table column names.</i>
------------	---------------------------------

Description

List table column names.

Usage

```
listFields(db, name, ...)
```

Arguments

db	rocker object
name	Table name
...	Optional, additional suitable parameters passed to <code>DBI::dbListFields()</code>

Value

Column names

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::listFields(db, "mtcars")
rocker::disconnect(db)
rocker::unloadDriver(db)
```

listObjects	<i>List database objects.</i>
-------------	-------------------------------

Description

List database objects.

Usage

```
listObjects(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to DBI::dbListObjects()

Value

List of objects

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::listObjects(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

listTables	<i>List database tables.</i>
------------	------------------------------

Description

List database tables.

Usage

```
listTables(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbListTables()</code>

Value

List of objects

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::listTables(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

newDB	<i>newDB</i>
-------	--------------

Description

Function generates a new [R6](#) database handling interface with [DBI](#) backend. For more information, see [rocker](#) class description.

Usage

```
newDB(verbose = TRUE, id = NULL, ...)
```

Arguments

verbose	TRUE or FALSE. Switch text output on / off.
id	Optional object ID/name
...	Not used yet

Value

New instance of rocker class

See Also

Other rocker: [rocker-R6-class](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#)

Examples

```
db <- rocker::newDB()
```

readTable	<i>Read table.</i>
-----------	--------------------

Description

Read table.

Usage

```
readTable(db, name, ...)
```

Arguments

db	rocker object
name	Table name
...	Optional, additional suitable parameters passed to DBI::dbReadTable()

Value

Table

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
output <- rocker::readTable(db, "mtcars")
rocker::disconnect(db)
rocker::unloadDriver(db)
```

removeTable	<i>Remove table.</i>
-------------	----------------------

Description

Remove table.

Usage

```
removeTable(db, name, ...)
```

Arguments

db	rocker object
name	Table name
...	Optional, additional suitable parameters passed to DBI::dbRemoveTable()

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::removeTable(db, "mtcars")
rocker::disconnect(db)
rocker::unloadDriver(db)
```

rocker-R6-class

'rocker' Database Interface R6 Class

Description

R6 class interface for handling database connections using [DBI](#) package as backend. The class allows handling of connections to e.g. PostgreSQL, MariaDB and SQLite.

Format

[R6Class](#)

Active bindings

`.drv` Read only [DBI::DBIDriver-class](#) object or NULL. It is recommended not to use this object! For advanced user, object can be used for direct execution of functions from DBI package.

`.con` Read only [DBI::DBIConnection-class](#) object or NULL. It is recommended not to use this object! For advanced user, object can be used for direct execution of functions from DBI package.

`.res` Read only [DBI::DBIResult-class](#) object or NULL. It is recommended not to use this object! For advanced user, object can be used for direct execution of functions from DBI package.

`transaction` Read only TRUE or FALSE. Information on pending transaction.

`info` Read only driver package and connection parameter information list.

`verbose` TRUE or FALSE. Switch text output on / off.

`id` Optional object ID/name

`validateQuery` SQL statement used in `validateCon`

Methods**Public methods:**

- rocker\$new()
- rocker\$print()
- rocker\$setupDriver()
- rocker\$setupPostgreSQL()
- rocker\$setupMariaDB()
- rocker\$setupSQLite()
- rocker\$unloadDriver()
- rocker\$scanConnect()
- rocker\$connect()
- rocker\$disconnect()
- rocker\$sendQuery()
- rocker\$getQuery()
- rocker\$sendStatement()
- rocker\$execute()
- rocker\$fetch()
- rocker\$hasCompleted()
- rocker\$getRowsAffected()
- rocker\$getRowCount()
- rocker\$columnInfo()
- rocker\$getStatement()
- rocker\$clearResult()
- rocker\$begin()
- rocker\$commit()
- rocker\$rollback()
- rocker\$getInfoDrv()
- rocker\$getInfoCon()
- rocker\$getInfoRes()
- rocker\$isValidDrv()
- rocker\$isValidCon()
- rocker\$isValidRes()
- rocker\$validateCon()
- rocker\$createTable()
- rocker\$appendTable()
- rocker\$writeTable()
- rocker\$readTable()
- rocker\$removeTable()
- rocker\$existsTable()
- rocker\$listFields()
- rocker\$listObjects()
- rocker\$listTables()

Method `new()`: Generate new instance of class.

Usage:

```
rocker$new(verbose = TRUE, id = NULL, ...)
```

Arguments:

`verbose` TRUE or FALSE. Switch text output on / off.

`id` Optional object ID/name

... Not used yet

Returns: New instance of class

Method `print()`: Print object information.

Usage:

```
rocker$print()
```

Returns: Invisible self

Method `setupDriver()`: Setup database driver and define connection parameters.

Usage:

```
rocker$setupDriver(drv, protect = c("password", "user"), ...)
```

Arguments:

`drv` Driver object from suitable package e.g. `RPostgres::Postgres()`, `RMariaDB::MariaDB()` and `RSQLite::SQLite()`

`protect` Parameters to be hidden

... Suitable parameters passed to `DBI::dbConnect()` e.g. host, port, dbname, user and password

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupDriver(
  drv = RSQLite::SQLite(),
  dbname = ":memory:"
)
db$unloadDriver()
```

Method `setupPostgreSQL()`: Setup database driver and define connection parameters for PostgreSQL using `RPostgres` package. Wrapper for `setupDriver()` function.

Usage:

```
rocker$setupPostgreSQL(
  host = "127.0.0.1",
  port = "5432",
  dbname = "mydb",
  user = "postgres",
  password = "password",
  protect = c("password", "user"),
  ...
)
```


Arguments:

host Host name or IP number
 port Port number
 dbname Database name
 user User name
 password Password
 protect Parameters to be hidden
 ... Optional, additional suitable parameters passed to [DBI::dbConnect\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupPostgreSQL(
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres", password = "password"
)
db$unloadDriver()
```

Method `setupMariaDB()`: Setup database driver and define connection parameters for MariaDB using [RMariaDB](#) package. Wrapper for `setupDriver()` function.

Usage:

```
rocker$setupMariaDB(
  host = "127.0.0.1",
  port = "3306",
  dbname = "mydb",
  user = "root",
  password = "password",
  protect = c("password", "user"),
  ...
)
```

Arguments:

host Host name or IP number
 port Port number
 dbname Database name
 user User name
 password Password
 protect Parameters to be hidden
 ... Optional, additional suitable parameters passed to [DBI::dbConnect\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupMariaDB(
  host = "127.0.0.1", port = "3306", dbname = "mydb",
  user = "root", password = "password"
)
db$unloadDriver()
```

Method `setupSQLite()`: Setup database driver and define connection parameters for SQLite using [RSQLite](#) package. Wrapper for `setupDriver()` function.

Usage:

```
rocker$setupSQLite(dbname = ":memory:", protect = c("password", "user"), ...)
```

Arguments:

`dbname` Database name

`protect` Parameters to be hidden

... Optional, additional suitable parameters passed to [DBI::dbConnect\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite(
  dbname = ":memory:"
)
db$unloadDriver()
```

Method `unloadDriver()`: Reset database driver and connection parameters.

Usage:

```
rocker$unloadDriver(...)
```

Arguments:

... Optional, suitable parameters passed to [DBI::dbUnloadDriver\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$unloadDriver()
```

Method `canConnect()`: Test connection parameters.

Usage:

```
rocker$canConnect(...)
```

Arguments:

... Optional, suitable parameters passed to [DBI::dbCanConnect\(\)](#)

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$canConnect()
db$unloadDriver()
```

Method `connect()`: Establish database connection using stored parameters.

Usage:

```
rocker$connect(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbConnect()`

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$disconnect()
db$unloadDriver()
```

Method `disconnect()`: Disconnect database.

Usage:

```
rocker$disconnect(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbDisconnect()`

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$disconnect()
db$unloadDriver()
```

Method `sendQuery()`: Send SQL query to database.

Usage:

```
rocker$sendQuery(statement, ...)
```

Arguments:

statement SQL query (SELECT)

... Optional, additional suitable parameters passed to `DBI::dbSendQuery()`

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `getQuery()`: Retrieve SQL query from database. Combination of functions `sendQuery()`, `fetch()` and `clearResult()`. If required, database is automatically connected and disconnected.

Usage:

```
rocker$getQuery(statement, n = -1, ...)
```

Arguments:

statement SQL query (SELECT)

n Number of record to be fetched at once. All records will be fetched.

... Optional, additional suitable parameters passed to [DBI::dbSendQuery\(\)](#)

Returns: Records

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
output <- db$getQuery("SELECT * FROM mtcars;")
db$disconnect()
db$unloadDriver()
```

Method `sendStatement()`: Send SQL statement to database.

Usage:

```
rocker$sendStatement(statement, ...)
```

Arguments:

statement SQL statement (UPDATE, DELETE, INSERT INTO, ...)

... Optional, additional suitable parameters passed to [DBI::dbSendStatement\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `execute()`: Execute SQL statement in database. Combination of functions `execute` and `clearResult`. If required, database is automatically connected and disconnected.

Usage:

```
rocker$execute(statement, ...)
```

Arguments:

statement SQL statement (UPDATE, DELETE, INSERT INTO, ...)

... Optional, additional suitable parameters passed to [DBI::dbSendStatement\(\)](#)

Returns: Number of affected rows

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$execute("DELETE FROM mtcars WHERE gear = 3;")
db$disconnect()
db$unloadDriver()
```

Method `fetch()`: Fetch SQL query result from database.

Usage:

```
rocker$fetch(n = -1, ...)
```

Arguments:

n Number of record to be fetched

... Optional, additional suitable parameters passed to `DBI::dbFetch()`

Returns: Records

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `hasCompleted()`: Information whether all records were retrieved.

Usage:

```
rocker$hasCompleted(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbHasCompleted()`

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch(5)
db$hasCompleted()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `getRowsAffected()`: Information on number of affected rows.

Usage:

```
rocker$getRowsAffected(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbGetRowsAffected\(\)](#)

Returns: Number of affected rows

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$getRowsAffected()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `getRowCount()`: Information on number of retrieved rows.

Usage:

```
rocker$getRowCount(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbGetRowCount\(\)](#)

Returns: Number of retrieved rows

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$getRowCount()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `columnInfo()`: Information on query result columns.

Usage:

```
rocker$columnInfo(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbColumnInfo\(\)](#)

Returns: Information table

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$columnInfo()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `getStatement()`: Information on sent statement.

Usage:

```
rocker$getStatement(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbGetStatement()`

Returns: Statement text

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$getStatement()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `clearResult()`: Clear query or statement result.

Usage:

```
rocker$clearResult(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbClearResult()`

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `begin()`: Begin transaction.

Usage:

```
rocker$begin(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbBegin\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$begin()
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$commit()
db$disconnect()
db$unloadDriver()
```

Method `commit()`: Commit transaction.

Usage:

```
rocker$commit(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbCommit\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$begin()
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$commit()
db$disconnect()
db$unloadDriver()
```

Method `rollback()`: Rollback transaction.

Usage:

```
rocker$rollback(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbRollback\(\)](#)

Returns: Invisible self

Examples:


```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$begin()
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$rollback()
db$disconnect()
db$unloadDriver()
```

Method `getInfoDrv()`: Information on driver object.

Usage:

```
rocker$getInfoDrv(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbGetInfo()`

Returns: Information list

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$getInfoDrv()
db$unloadDriver()
```

Method `getInfoCon()`: Information on connection object.

Usage:

```
rocker$getInfoCon(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbGetInfo()`

Returns: Information list

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$getInfoCon()
db$disconnect()
db$unloadDriver()
```

Method `getInfoRes()`: Information on result object.

Usage:

```
rocker$getInfoRes(...)
```

Arguments:

... Optional, additional suitable parameters passed to `DBI::dbGetInfo()`

Returns: Information list

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$getInfoRes()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method `isValidDrv()`: Check driver object.

Usage:

```
rocker$isValidDrv(onLostNull = FALSE, ...)
```

Arguments:

`onLostNull` TRUE or FALSE. If driver lost, set `.drv` to NULL

... Optional, additional suitable parameters passed to `DBI::dbIsValid()`

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$isValidDrv()
db$unloadDriver()
```

Method `isValidCon()`: Check connection object.

Usage:

```
rocker$isValidCon(onLostNull = FALSE, ...)
```

Arguments:

`onLostNull` TRUE or FALSE. If connection lost, set `.con` to NULL

... Optional, additional suitable parameters passed to `DBI::dbIsValid()`

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$isValidCon()
db$disconnect()
db$unloadDriver()
```

Method `isValidRes()`: Check result object.

Usage:

```
rocker$isValidRes(onLostNull = FALSE, ...)
```

Arguments:

onLostNull TRUE or FALSE. If result lost, set .res to NULL
 ... Optional, additional suitable parameters passed to [DBI::dbIsValid\(\)](#)

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$isValidRes()
db$clearResult()
db$disconnect()
db$unloadDriver()
```

Method validateCon(): Check if an earlier opened connection is still open.

Usage:

```
rocker$validateCon(statement = NULL, onLostNull = FALSE, ...)
```

Arguments:

statement Optional SQL statement. If not set default validateQuery will be used.

onLostNull TRUE or FALSE. If connection lost, set .con to NULL

... Not used yet

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$validateCon()
db$disconnect()
db$unloadDriver()
```

Method createTable(): Create empty formatted table.

Usage:

```
rocker$createTable(name, fields, ...)
```

Arguments:

name Table name

fields Template data.frame

... Optional, additional suitable parameters passed to [DBI::dbCreateTable\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$createTable("mtcars", mtcars)
db$disconnect()
db$unloadDriver()
```

Method `appendTable()`: Append data to table.

Usage:

```
rocker$appendTable(name, value, ...)
```

Arguments:

name Table name

value Values data.frame

... Optional, additional suitable parameters passed to `DBI::dbAppendTable()`

Returns: Number of appended rows invisibly

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$createTable("mtcars", mtcars)
db$appendTable("mtcars", mtcars)
db$disconnect()
db$unloadDriver()
```

Method `writeTable()`: Write data to table.

Usage:

```
rocker$writeTable(name, value, ...)
```

Arguments:

name Table name

value Values data.frame

... Optional, additional suitable parameters passed to `DBI::dbWriteTable()`

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$disconnect()
db$unloadDriver()
```

Method `readTable()`: Read table.

Usage:

```
rocker$readTable(name, ...)
```

Arguments:

name Table name

... Optional, additional suitable parameters passed to `DBI::dbReadTable()`

Returns: Table

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
output <- db$readTable("mtcars")
db$disconnect()
db$unloadDriver()
```

Method `removeTable()`: Remove table.

Usage:

```
rocker$removeTable(name, ...)
```

Arguments:

name Table name

... Optional, additional suitable parameters passed to [DBI::dbRemoveTable\(\)](#)

Returns: Invisible self

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$removeTable("mtcars")
db$disconnect()
db$unloadDriver()
```

Method `existsTable()`: Check if table exists.

Usage:

```
rocker$existsTable(name, ...)
```

Arguments:

name Table name

... Optional, additional suitable parameters passed to [DBI::dbExistsTable\(\)](#)

Returns: TRUE or FALSE

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$existsTable("mtcars")
db$disconnect()
db$unloadDriver()
```

Method `listFields()`: List table column names.

Usage:

```
rocker$listFields(name, ...)
```

Arguments:

name Table name
... Optional, additional suitable parameters passed to [DBI::dbListFields\(\)](#)

Returns: Column names

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$listFields("mtcars")
db$disconnect()
```

Method `listObjects()`: List database objects.

Usage:

```
rocker$listObjects(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbListObjects\(\)](#)

Returns: List of objects

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$listObjects()
db$disconnect()
```

Method `listTables()`: List database tables.

Usage:

```
rocker$listTables(...)
```

Arguments:

... Optional, additional suitable parameters passed to [DBI::dbListTables\(\)](#)

Returns: List of objects

Examples:

```
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$listTables()
db$disconnect()
```

See Also

Other rocker: [newDB\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#)

Examples

```

# New database handling object
db <- rocker::newDB()
# Setup SQLite database
db$setupSQLite()
# Open connection
db$connect()
# Write table
db$writeTable("mtcars", mtcars)
# Get query
output <- db$getQuery("SELECT * FROM mtcars;")
# Close connection
db$disconnect()
# Reset database handling object
db$unloadDriver()

## -----
## Method `rocker$setupDriver`
## -----

db <- rocker::newDB()
db$setupDriver(
  drv = RSQLite::SQLite(),
  dbname = ":memory:"
)
db$unloadDriver()

## -----
## Method `rocker$setupPostgreSQL`
## -----

db <- rocker::newDB()
db$setupPostgreSQL(
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres", password = "password"
)
db$unloadDriver()

## -----
## Method `rocker$setupMariaDB`
## -----

db <- rocker::newDB()
db$setupMariaDB(
  host = "127.0.0.1", port = "3306", dbname = "mydb",
  user = "root", password = "password"
)
db$unloadDriver()

## -----
## Method `rocker$setupSQLite`
## -----

```

```

db <- rocker::newDB()
db$setupSQLite(
  dbname = ":memory:"
)
db$unloadDriver()

## -----
## Method `rocker$unloadDriver`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$unloadDriver()

## -----
## Method `rocker$scanConnect`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$scanConnect()
db$unloadDriver()

## -----
## Method `rocker$connect`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$disconnect`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$sendQuery`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")

```



```

output <- db$fetch()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$getQuery`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
output <- db$getQuery("SELECT * FROM mtcars;")
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$sendStatement`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$execute`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$execute("DELETE FROM mtcars WHERE gear = 3;")
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$fetch`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$clearResult()

```

```

db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$hasCompleted`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch(5)
db$hasCompleted()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$getRowsAffected`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$getRowsAffected()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$getRowCount`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$getRowCount()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$columnInfo`
## -----

db <- rocker::newDB()
db$setupSQLite()

```

```

db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$columnInfo()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$getStatement`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$getStatement()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$clearResult`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
output <- db$fetch()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$begin`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$begin()
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$commit()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$commit`

```

```

## -----
db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$begin()
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$commit()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$rollback`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$begin()
db$sendStatement("DELETE FROM mtcars WHERE gear = 3;")
db$clearResult()
db$rollback()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$getInfoDrv`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$getInfoDrv()
db$unloadDriver()

## -----
## Method `rocker$getInfoCon`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$getInfoCon()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$getInfoRes`
## -----

db <- rocker::newDB()

```

```

db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$getInfoRes()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$isValidDrv`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$isValidDrv()
db$unloadDriver()

## -----
## Method `rocker$isValidCon`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$isValidCon()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$isValidRes`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$sendQuery("SELECT * FROM mtcars;")
db$isValidRes()
db$clearResult()
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$validateCon`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$validateCon()
db$disconnect()
db$unloadDriver()

```

```
## -----  
## Method `rocker$createTable`  
## -----  
  
db <- rocker::newDB()  
db$setupSQLite()  
db$connect()  
db$createTable("mtcars", mtcars)  
db$disconnect()  
db$unloadDriver()  
  
## -----  
## Method `rocker$appendTable`  
## -----  
  
db <- rocker::newDB()  
db$setupSQLite()  
db$connect()  
db$createTable("mtcars", mtcars)  
db$appendTable("mtcars", mtcars)  
db$disconnect()  
db$unloadDriver()  
  
## -----  
## Method `rocker$writeTable`  
## -----  
  
db <- rocker::newDB()  
db$setupSQLite()  
db$connect()  
db$writeTable("mtcars", mtcars)  
db$disconnect()  
db$unloadDriver()  
  
## -----  
## Method `rocker$readTable`  
## -----  
  
db <- rocker::newDB()  
db$setupSQLite()  
db$connect()  
db$writeTable("mtcars", mtcars)  
output <- db$readTable("mtcars")  
db$disconnect()  
db$unloadDriver()  
  
## -----  
## Method `rocker$removeTable`  
## -----  
  
db <- rocker::newDB()  
db$setupSQLite()
```

```
db$connect()
db$writeTable("mtcars", mtcars)
db$removeTable("mtcars")
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$existsTable`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$existsTable("mtcars")
db$disconnect()
db$unloadDriver()

## -----
## Method `rocker$listFields`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$listFields("mtcars")
db$disconnect()

## -----
## Method `rocker$listObjects`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$listObjects()
db$disconnect()

## -----
## Method `rocker$listTables`
## -----

db <- rocker::newDB()
db$setupSQLite()
db$connect()
db$writeTable("mtcars", mtcars)
db$listTables()
db$disconnect()
```

rocker-README

README

Description

How-to and examples

Details

Please read me.

Installation

Installation of current released version from CRAN

```
install.packages("rocker")
```

Installation of current development version from GitHub

```
install.packages("devtools")
devtools::install_github("nikolaus77/rocker")
```

New *rocker* class object

Create new *rocker* database handling object

Option 1

```
db <- rocker::newDB() # New database handling object
```

```
## dctr | New object
```

Option 2

```
db <- rocker::rocker$new() # New database handling object
```

```
## dctr | New object
```

Terminal output

Controlling terminal output

```
db <- rocker::newDB(verbose = TRUE) # New database handling object
```

```
## dctr | New object
```

```
db$setupPostgreSQL()
```



```
## Dctr | Driver load RPostgres

db$unloadDriver()

## dctr | Driver unload RPostgres

db$verbose <- FALSE # Terminal output off
db$setupPostgreSQL()
db$unloadDriver()

db$verbose <- TRUE # Terminal output on (default)
db$setupPostgreSQL()

## Dctr | Driver load RPostgres

db$unloadDriver()

## dctr | Driver unload RPostgres
```

Structure of terminal output

```
Dctr | Driver load RSQLite
D          = Driver      (D = loaded,   d = not set)
c          = Connection (C = opened,   c = closed)
t          = Transaction (T = active,   t = no tranastion)
r          = Result      (R = available, r = no result)
      Driver load RSQLite = Message text
```

Optional object ID

Optionally, rocker object can be labeled with an ID. This can be helpful in case terminal output of multiple rocker objects need to be distinguished.

```
db1 <- rocker::newDB(id = "myDB 1") # New database handling object with ID

## myDB 1 | dctr | New object id myDB 1

db2 <- rocker::newDB(id = "myDB 2") # New database handling object with ID

## myDB 2 | dctr | New object id myDB 2

db1$setupPostgreSQL()

## myDB 1 | Dctr | Driver load RPostgres

db2$setupMariaDB()

## myDB 2 | Dctr | Driver load RMariaDB
```

```
db1$unloadDriver()

## myDB 1 | dctr | Driver unload RPostgres

db2$unloadDriver()

## myDB 2 | dctr | Driver unload RMariaDB

db1$id <- NULL # Remove ID
db1$setupSQLite()

## Dctr | Driver load RSQLite

db1$unloadDriver()

## dctr | Driver unload RSQLite

db1$id <- "newID 1" # Add new ID
db1$setupSQLite()

## newID 1 | Dctr | Driver load RSQLite

db1$unloadDriver()

## newID 1 | dctr | Driver unload RSQLite
```

Object properties

Object properties are stored in the info field and can be displayed by print function.

```
db <- rocker::newDB() # New database handling object

## dctr | New object

db$setupPostgreSQL()

## Dctr | Driver load RPostgres

db$info

## $package
## [1] "RPostgres"
##
## $host
## [1] "127.0.0.1"
##
## $port
## [1] "5432"
##
## $dbname
## [1] "mydb"
```

```
db

## object
##   id          null
##   verbose     true
##   validateQuery null
## database
##   package     RPostgres
##   host        127.0.0.1
##   port        5432
##   dbname      mydb
## status
##   driver      true
##   connection  false
##   transaction false
##   result      false

db$print()

## object
##   id          null
##   verbose     true
##   validateQuery null
## database
##   package     RPostgres
##   host        127.0.0.1
##   port        5432
##   dbname      mydb
## status
##   driver      true
##   connection  false
##   transaction false
##   result      false

print(db)

## object
##   id          null
##   verbose     true
##   validateQuery null
## database
##   package     RPostgres
##   host        127.0.0.1
##   port        5432
##   dbname      mydb
## status
##   driver      true
##   connection  false
##   transaction false
##   result      false
```

```
db$unloadDriver()

## dctr | Driver unload RPostgres
```

Connection validation – Is the earlier opened database connection still open?

```
db <- rocker::newDB() # New database handling object

## dctr | New object

db$setupSQLite()

## Dctr | Driver load RSQLite

db$print()

## object
##   id          null
##  verbose      true
##  validateQuery null
## database
##  package      RSQLite
##  dbname        :memory:
## status
##  driver        true
##  connection    false
##  transaction   false
##  result        false
```

During connection setup, a validateQuery is looked up automatically.

```
db$connect()

## DCtr | Database connected

db$print()

## object
##   id          null
##  verbose      true
##  validateQuery SELECT 1
## database
##  package      RSQLite
##  dbname        :memory:
## status
##  driver        true
##  connection    true
##  transaction   false
##  result        false
```

```
Discovered validateQuery
db$validateQuery
## [1] "SELECT 1"

Validate connection
db$validateCon()
## Dctr | Connection valid true

## [1] TRUE

If required, validateQuery can be defined manually.
db$validateQuery <- "SELECT 2"
db$validateCon()

## Dctr | Connection valid true

## [1] TRUE

db$print()

## object
##   id          null
##  verbose      true
##  validateQuery SELECT 2
## database
##  package      RSQLite
##  dbname       :memory:
## status
##  driver       true
##  connection   true
##  transaction  false
##  result       false

Clean up
db$disconnect()
## Dctr | Database disconnected

db$validateCon()
## Dctr | Connection valid false

## [1] FALSE

db$unloadDriver()
## dctr | Driver unload RSQLite
```

Additional packages and database types

The listed packages are required for some functions of *rocker*.

***RSQLite* package:**

RSQLite package for handling of SQLite database connections. It is required for the `setupSQLite()` function of *rocker* class.

```
install.packages("RSQLite")
```

Setup database

Option 1

```
db <- rocker::newDB() # New database handling object
```

```
## dctr | New object
```

```
db$setupSQLite( # Setup SQLite database
  dbname = ":memory:"
)
```

```
## Dctr | Driver load RSQLite
```

```
db$unloadDriver() # Reset database handling object
```

```
## dctr | Driver unload RSQLite
```

Option 2

```
db <- rocker::newDB() # New database handling object
```

```
## dctr | New object
```

```
db$setupDriver( # Setup SQLite database
  drv = RSQLite::SQLite(),
  dbname = ":memory:"
)
```

```
## Dctr | Driver load RSQLite
```

```
db$unloadDriver() # Reset database handling object
```

```
## dctr | Driver unload RSQLite
```

***RPostgres* package:**

RPostgres package for handling of PostgreSQL database connections. It is required for the `setupPostgreSQL()` function of *rocker* class.

```
install.packages("RPostgres")
```

Setup database

Option 1

```

db <- rocker::newDB() # New database handling object
#> dctr | New object
db$setupPostgreSQL( # Setup PostgreSQL database
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres", password = "password"
)
#> Dctr | Driver load RPostgres
db$unloadDriver() # Reset database handling object
#> dctr | Driver unload RPostgres

```

Option 2

```

db <- rocker::newDB() # New database handling object
#> dctr | New object
db$setupDriver( # Setup PostgreSQL database
  drv = RPostgres::Postgres(),
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres", password = "password"
)
#> Dctr | Driver load RPostgres
db$unloadDriver() # Reset database handling object
#> dctr | Driver unload RPostgres

```

RMariaDB package:

RMariaDB package for handling of MariaDB and MySQL database connections. It is required for the `setupMariaDB()` function of *rocker* class.

```
install.packages("RMariaDB")
```

Setup database

Option 1

```

db <- rocker::newDB() # New database handling object
#> dctr | New object
db$setupMariaDB( # Setup MariaDB database
  host = "127.0.0.1", port = "3306", dbname = "mydb",
  user = "root", password = "password"
)
#> Dctr | Driver load RMariaDB
db$unloadDriver() # Reset database handling object
#> dctr | Driver unload RMariaDB

```

Option 2

```

db <- rocker::newDB() # New database handling object
#> dctr | New object
db$setupDriver( # Setup MariaDB database
  drv = RMariaDB::MariaDB(),
  host = "127.0.0.1", port = "3306", dbname = "mydb",
  user = "root", password = "password"
)

```

```
#> Dctr | Driver load RMariaDB
db$unloadDriver() # Reset database handling object
#> dctr | Driver unload RMariaDB
```

crayon package:

The *crayon* package is required for colored terminal output. If missing terminal output is monochrome.

```
install.packages("crayon")
```

Database connection

There are different ways to open a connection and to get data.

Prepare database with a table

```
db <- rocker::newDB() # New database handling object

## dctr | New object

db$setupSQLite(dbname = tempfile()) # Setup SQLite database

## Dctr | Driver load RSQLite

db$connect() # Open connection

## DCtr | Database connected

db$writeTable("mtcars", mtcars) # Create table for testing

## DCtr | Write table mtcars columns mpg, cyl, disp, hp, drat, wt, qsec, vs, am, gear, carb rows 32

db$disconnect() # Close connection

## Dctr | Database disconnected
```

Example 1

Get query with automatic connection / disconnection

```
output <- db$getQuery("SELECT * FROM mtcars;") # Get query

## DCtr | Database connected
## DCtR | Send query 21 characters
## DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
## DCtR | Rows fetched 32
## DCtR | Has completed yes
## DCtr | Clear result
## Dctr | Database disconnected
```


Example 2

Get query with manual connection / disconnection

```
db$connect() # Open connection

## DCtr | Database connected

output1 <- db$getQuery("SELECT * FROM mtcars;") # Get query 1

## DCtR | Send query 21 characters
## DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
## DCtR | Rows fetched 32
## DCtR | Has completed yes
## DCtr | Clear result

output2 <- db$getQuery("SELECT * FROM mtcars;", 15) # Get query 2

## DCtR | Send query 21 characters
## DCtR | Fetch rows 15 -> Received 15 rows, 11 columns, 3416 bytes
## DCtR | Rows fetched 15
## DCtR | Has completed no
## DCtR | Fetch rows 15 -> Received 15 rows, 11 columns, 3416 bytes
## DCtR | Rows fetched 30
## DCtR | Has completed no
## DCtR | Fetch rows 15 -> Received 2 rows, 11 columns, 2184 bytes
## DCtR | Rows fetched 32
## DCtR | Has completed yes
## DCtr | Clear result

db$disconnect() # Close connection

## Dctr | Database disconnected
```

Example 3

Function `getQuery()` is a combination of functions `sendQuery()`, `fetch()` and `clearResult()`.

```
db$connect() # Open connection

## DCtr | Database connected

db$sendQuery("SELECT * FROM mtcars;") # Send query

## DCtR | Send query 21 characters

output <- db$fetch() # Fetch result
```

```

## DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes

db$clearResult() # Clean up result

## DCtr | Clear result

db$disconnect() # Close connection

## Dctr | Database disconnected

Clean up

db$unloadDriver() # Reset database handling object

## dctr | Driver unload RSQLite

```

Password storage

Some efforts were undertaken to encrypt and to protect the password in the private area of the class. The class stores the password hidden and inaccessible. **Please let me know, in case you discover a way how to access the password!**

```

db <- rocker::newDB() # New database handling object
#> dctr | New object
db$setupDriver( # Setup PostgreSQL database with stored password (password and user are hidden - default
  RPostgres::Postgres(),
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres", password = "password",
  protect = c("password", "user")
)
#> Dctr | Driver load RPostgres

db$connect() # Open connection 1; Password is stored in the class and does not need to be provided.
#> DCtr | Database connected
output1 <- db$getQuery("SELECT * FROM mtcars;") # Get query 1
#> DCtR | Send query 21 characters
#> DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
#> DCtR | Rows fetched 32
#> DCtR | Has completed yes
#> DCtr | Clear result
db$disconnect() # Close connection 1
#> Dctr | Database disconnected

db$connect() # Open connection 2; Password is stored in the class and does not need to be provided.
#> DCtr | Database connected
output2 <- db$getQuery("SELECT * FROM mtcars;") # Get query 2
#> DCtR | Send query 21 characters
#> DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes

```

```
#> DCtR | Rows fetched 32
#> DCtR | Has completed yes
#> DCtr | Clear result
db$disconnect() # Close connection 2
#> Dctr | Database disconnected
```

```
db$unloadDriver() # Reset database handling object
#> dctr | Driver unload RPostgres
```

In case you do not want to store the password in the class, you will need to provide it each time a connection is opened.

```
db <- rocker::newDB() # New database handling object
#> dctr | New object
db$setupDriver( # Setup PostgreSQL database without stored password
  RPostgres::Postgres(),
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres"
)
#> Dctr | Driver load RPostgres
```

```
db$connect(password = "password") # Open connection 1; Password needs to be provided.
#> DCtR | Database connected
output1 <- db$getQuery("SELECT * FROM mtcars;") # Get query 1
#> DCtR | Send query 21 characters
#> DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
#> DCtR | Rows fetched 32
#> DCtR | Has completed yes
#> DCtr | Clear result
db$disconnect() # Close connection 1
#> Dctr | Database disconnected
```

```
db$connect(password = "password") # Open connection 2; Password needs to be provided.
#> DCtR | Database connected
output2 <- db$getQuery("SELECT * FROM mtcars;") # Get query 2
#> DCtR | Send query 21 characters
#> DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
#> DCtR | Rows fetched 32
#> DCtR | Has completed yes
#> DCtr | Clear result
db$disconnect() # Close connection 2
#> Dctr | Database disconnected
```

```
db$unloadDriver() # Reset database handling object
#> dctr | Driver unload RPostgres
```

DBI objects

rocker class encapsulates the *DBI* objects driver, connection and result. If required, these objects can be directly used with *DBI* functions. **However, it is recommended to use this option with care!** Direct usage of *DBI* functions, may disrupt proper function of *rocker* class. Many *DBI* functions are implemented in *rocker* class. Whenever possible, use the *rocker* class functions.

Prepare object

```
db <- rocker::newDB() # New database handling object

## dctr | New object

db$.drv # Empty driver

## NULL

db$.con # Empty connection

## NULL

db$.res # Empty result

## NULL

DBIDriver-class:

db$setupSQLite() # Setup SQLite database

## Dctr | Driver load RSQLite

db$.drv # 'DBI' DBIDriver-class

## <SQLiteDriver>

db$getInfoDrv() # 'rocker' class function

## Dctr | Driver info 2.2.16 (driver.version), 3.39.2 (client.version)

## $driver.version
## [1] '2.2.16'
##
## $client.version
## [1] '3.39.2'

DBI::dbGetInfo(db$.drv) # Direct usage of 'DBI' function on 'rocker' class

## $driver.version
## [1] '2.2.16'
##
## $client.version
## [1] '3.39.2'
```

```
RSQLite::dbGetInfo(db$.drv) # Direct usage of driver package, 'RSQLite', function on 'rocker' class
## $driver.version
## [1] '2.2.16'
##
## $client.version
## [1] '3.39.2'

DBIConnection-class:

db$connect() # Open connection
## DCtr | Database connected

db$.con # 'DBI' DBIConnection-class
## <SQLiteConnection>
## Path: :memory:
## Extensions: TRUE

db$getInfoCon() # 'rocker' class function
## DCtr | Connection info 3.39.2 (db.version), :memory: (dbname), NA (username), NA (host), NA (port)

## $db.version
## [1] "3.39.2"
##
## $dbname
## [1] ":memory:"
##
## $username
## [1] NA
##
## $host
## [1] NA
##
## $port
## [1] NA

DBI::dbGetInfo(db$.con) # Direct usage of 'DBI' function on 'rocker' class
## $db.version
## [1] "3.39.2"
##
## $dbname
## [1] ":memory:"
##
## $username
## [1] NA
##
## $host
## [1] NA
```

```

##
## $port
## [1] NA

RSQLite::dbGetInfo(db$.con) # Direct usage of driver package, 'RSQLite', function on 'rocker' class
## $db.version
## [1] "3.39.2"
##
## $dbname
## [1] ":memory:"
##
## $username
## [1] NA
##
## $host
## [1] NA
##
## $port
## [1] NA

Prepare table

db$writeTable("mtcars", mtcars) # Create table for testing
## DCtr | Write table mtcars columns mpg, cyl, disp, hp, drat, wt, qsec, vs, am, gear, carb rows 32

DBIResult-class:

db$sendQuery("SELECT * FROM mtcars;") # Send query
## DCtR | Send query 21 characters

db$.res # 'DBI' DBIResult-class

## <SQLiteResult>
##   SQL  SELECT * FROM mtcars;
##   ROWS Fetched: 0 [incomplete]
##       Changed: 0

db$getInfoRes() # 'rocker' class function
## DCtR | Result info SELECT * FROM mtcars; (statement), 0 (row.count), 0 (rows.affected), FALSE (has.c

## $statement
## [1] "SELECT * FROM mtcars;"
##
## $row.count
## [1] 0
##
## $rows.affected
## [1] 0
##
## $has.completed
## [1] FALSE

```

```
DBI::dbGetInfo(db$.res) # Direct usage of 'DBI' function on 'rocker' class

## $statement
## [1] "SELECT * FROM mtcars;"
##
## $row.count
## [1] 0
##
## $rows.affected
## [1] 0
##
## $has.completed
## [1] FALSE

RSQLite::dbGetInfo(db$.res) # Direct usage of driver package, 'RSQLite', function on 'rocker' class

## $statement
## [1] "SELECT * FROM mtcars;"
##
## $row.count
## [1] 0
##
## $rows.affected
## [1] 0
##
## $has.completed
## [1] FALSE

Clean up

db$clearResult() # Clean up result

## Dctr | Clear result

db$.res # Empty result

## NULL

db$disconnect() # Close connection

## Dctr | Database disconnected

db$.con # Empty connection

## NULL

db$unloadDriver() # Reset database handling object

## dctr | Driver unload RSQLite

db$.drv # Empty driver

## NULL
```

DBI functions in rocker

Generally, *rocker* function names are related to *DBI* function names. In *rocker* functions, the leading **db** is removed.

In *DBI* most functions need to be supplied with a driver (*drv*), connection (*conn*) or result (*res*) object. In *rocker*, functions automatically access the corresponding objects (*.drv*, *.con* and *.res*) stored in the class.

DBI example

```
drv <- RSQLite::SQLite() # SQLite driver
DBI::dbCanConnect( # Test parameter
  drv = drv,
  dbname = ":memory:"
)

## [1] TRUE

con <- DBI::dbConnect( # Open connection
  drv = drv,
  dbname = ":memory:"
)
DBI::dbWriteTable(con, "mtcars", mtcars) # Create table for testing
res <- DBI::dbSendQuery(con, "SELECT * FROM mtcars;") # Send query
output <- DBI::dbFetch(res) # Fetch result
DBI::dbClearResult(res) # Clean up result
DBI::dbDisconnect(con) # Close connection
DBI::dbUnloadDriver(drv) # Unload driver
```

rocker example

```
db <- rocker::newDB(verbose = FALSE) # New database handling object
db$setupDriver( # Setup SQLite database
  drv = RSQLite::SQLite(),
  dbname = ":memory:"
)
db$canConnect() # Test parameter

## [1] TRUE

db$connect() # Open connection
db$writeTable("mtcars", mtcars) # Create table for testing
db$sendQuery("SELECT * FROM mtcars;") # Send query
output <- db$fetch() # Fetch result
db$clearResult() # Clean up result
db$disconnect() # Close connection
db$unloadDriver() # Reset database handling object
```


List of functions:

<i>rocker</i> function	Corresponding <i>DBI</i> function	<i>DBI</i> object used	Comment
initialize()	<i>none</i>	<i>none</i>	
print()	<i>none</i>	<i>none</i>	
setupDriver()	<i>none</i>	<i>driver from appropriate package</i>	Usually, par
setupPostgreSQL()	<i>none</i>	<i>none</i>	RPostgres::I
setupMariaDB()	<i>none</i>	<i>none</i>	RMariaDB::
setupSQLite()	<i>none</i>	<i>none</i>	RSQLite::S
unloadDriver()	dbUnloadDriver()	driver	
canConnect()	dbCanConnect()	driver	Usually, par
connect()	dbConnect()	driver	Usually, par
disconnect()	dbDisconnect()	connection	
sendQuery()	dbSendQuery()	connection	
getQuery()	Is not using dbGetQuery(), but has the same function	connection	Especially, c
sendStatement()	dbSendStatement()	connection	
execute()	Is not using dbExecute(), but has the same function	connection	Especially, c
fetch()	dbFetch()	result	
hasCompleted()	dbHasCompleted()	result	
getRowsAffected()	dbGetRowsAffected()	result	
getRowCount()	dbGetRowCount()	result	
columnInfo()	dbColumnInfo()	result	
getStatement()	dbGetStatement()	result	
clearResult()	dbClearResult()	result	
begin()	dbBegin()	connection	
commit()	dbCommit()	connection	
rollback()	dbRollback()	connection	
getInfoDrv()	dbGetInfo()	driver	
getInfoCon()	dbGetInfo()	connection	
getInfoRes()	dbGetInfo()	result	
isValidDrv()	dbIsValid()	driver	
isValidCon()	dbIsValid()	connection	
isValidRes()	dbIsValid()	result	
createTable()	dbCreateTable()	connection	
appendTable()	dbAppendTable()	connection	
writeTable()	dbWriteTable	connection	
readTable()	dbReadTable	connection	
removeTable()	dbRemoveTable()	connection	
existsTable()	dbExistsTable()	connection	
listFields()	dbListFields()	connection	
listObjects()	dbListObjects()	connection	
listTables()	dbListTables()	connection	

Transaction

Setup database and a table with 32 rows.

```
db <- rocker::newDB() # New database handling object
```

```
## dctr | New object

db$setupSQLite() # Setup SQLite database

## Dctr | Driver load RSQLite

db$connect() # Open connection

## DCtr | Database connected

db$writeTable("mtcars", mtcars) # Create table for testing

## DCtr | Write table mtcars columns mpg, cyl, disp, hp, drat, wt, qsec, vs, am, gear, carb rows 32

output <- db$getQuery("SELECT * FROM mtcars;") # Get query -> 32 rows

## DCtR | Send query 21 characters
## DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
## DCtR | Rows fetched 32
## DCtR | Has completed yes
## DCtr | Clear result

db$transaction # Transaction indicator

## [1] FALSE

Starting with a table with 32 rows, begin transaction 1. Delete 15 rows and commit transaction.
Operations results in a table with 17 rows.

db$begin() # Start transaction 1

## DCtR | Transaction begin

db$transaction # Transaction indicator

## [1] TRUE

AFFECTED <- db$execute("DELETE FROM mtcars WHERE gear = 3;") # Modify table -> 15 rows

## DCTR | Send statement 34 characters
## DCTR | Rows affected 15
## DCtR | Clear result

db$commit() # Commit transaction 1

## DCtr | Transaction commit
```

```
db$transaction # Transaction indicator

## [1] FALSE

output <- db$getQuery("SELECT * FROM mtcars;") # Get query -> 17 rows

## DcTr | Send query 21 characters
## DcTr | Fetch rows all -> Received 17 rows, 11 columns, 3504 bytes
## DcTr | Rows fetched 17
## DcTr | Has completed yes
## DcTr | Clear result

Starting with a table with 17 rows, begin transaction 2. Delete 5 rows and rollback transaction.
Operations results in a table with 17 rows.

db$begin() # Start transaction 2

## DcTr | Transaction begin

db$transaction # Transaction indicator

## [1] TRUE

AFFECTED <- db$execute("DELETE FROM mtcars WHERE gear = 5;") # Modify table -> 5 rows

## DCTR | Send statement 34 characters
## DCTR | Rows affected 5
## DcTr | Clear result

output <- db$getQuery("SELECT * FROM mtcars;") # Get query -> 12 rows

## DCTR | Send query 21 characters
## DCTR | Fetch rows all -> Received 12 rows, 11 columns, 3416 bytes
## DCTR | Rows fetched 12
## DCTR | Has completed yes
## DcTr | Clear result

db$rollback() # Rollback transaction 2

## DcTr | Transaction rollback

db$transaction # Transaction indicator

## [1] FALSE

output <- db$getQuery("SELECT * FROM mtcars;") # Get query -> 17 rows
```

```
## DCtR | Send query 21 characters
## DCtR | Fetch rows all -> Received 17 rows, 11 columns, 3504 bytes
## DCtR | Rows fetched 17
## DCtR | Has completed yes
## DCtr | Clear result
```

Clean up

```
db$disconnect() # Close connection
```

```
## Dctr | Database disconnected
```

```
db$unloadDriver() # Reset database handling object
```

```
## dctr | Driver unload RSQLite
```

Usage of S3 and R6 functions

Although *rocker* is a *R6* class, functions can be also accesses in classical *S3* way.

S3 example

```
library(rocker)
db <- newDB()
```

```
## dctr | New object
```

```
setupDriver(db, drv = RSQLite::SQLite(), dbname = ":memory:")
```

```
## Dctr | Driver load RSQLite
```

```
connect(db)
```

```
## DCtr | Database connected
```

```
writeTable(db, "mtcars", mtcars)
```

```
## DCtr | Write table mtcars columns mpg, cyl, disp, hp, drat, wt, qsec, vs, am, gear, carb rows 32
```

```
sendQuery(db, "SELECT * FROM mtcars;")
```

```
## DCtR | Send query 21 characters
```

```
output <- fetch(db)
```

```
## DCtR | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes
```

```
clearResult(db)
```

```
## Dctr | Clear result
disconnect(db)

## Dctr | Database disconnected
unloadDriver(db)

## dctr | Driver unload RSQLite

R6 example

db <- rocker::newDB()

## dctr | New object

db$setupDriver(drv = RSQLite::SQLite(), dbname = ":memory:")

## Dctr | Driver load RSQLite

db$connect()

## Dctr | Database connected

db$writeTable("mtcars", mtcars)

## Dctr | Write table mtcars columns mpg, cyl, disp, hp, drat, wt, qsec, vs, am, gear, carb rows 32

db$sendQuery("SELECT * FROM mtcars;")

## Dctr | Send query 21 characters

output <- db$fetch()

## Dctr | Fetch rows all -> Received 32 rows, 11 columns, 4824 bytes

db$clearResult()

## Dctr | Clear result

db$disconnect()

## Dctr | Database disconnected

db$unloadDriver()

## dctr | Driver unload RSQLite
```

See Also

Other rocker: [newDB\(\)](#), [rocker-R6-class](#), [rocker-S3-functions](#), [rocker-package](#)

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

rocker-S3-functions *'rocker' Database Interface R6 Class - S3 functions*

Description

R6 class interface for handling database connections using **DBI** package as backend. The class allows handling of connections to e.g. PostgreSQL, MariaDB and SQLite. Although rocker is a R6 class, functions can be also accessed in classical S3 way.

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Other rocker: [newDB\(\)](#), [rocker-R6-class](#), [rocker-README](#), [rocker-package](#)

Examples

```
# New database handling object
db <- rocker::newDB()
# Setup SQLite database
rocker::setupSQLite(db)
# Open connection
rocker::connect(db)
# Write table
rocker::writeTable(db, "mtcars", mtcars)
# Get query
output <- rocker::getQuery(db, "SELECT * FROM mtcars;")
# Close connection
rocker::disconnect(db)
# Reset database handling object
rocker::unloadDriver(db)
```

rollback	<i>Rollback transaction.</i>
----------	------------------------------

Description

Rollback transaction.

Usage

```
rollback(db, ...)
```

Arguments

db	rocker object
...	Optional, additional suitable parameters passed to <code>DBI::dbRollback()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::begin(db)
rocker::sendStatement(db, "DELETE FROM mtcars WHERE gear = 3;")
rocker::clearResult(db)
rocker::rollback(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

sendQuery	<i>Send SQL query to database.</i>
-----------	------------------------------------

Description

Send SQL query to database.

Usage

```
sendQuery(db, statement, ...)
```

Arguments

db	rocker object
statement	SQL query (SELECT)
...	Optional, additional suitable parameters passed to <code>DBI::dbSendQuery()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendQuery(db, "SELECT * FROM mtcars;")
output <- rocker::fetch(db)
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

sendStatement	<i>Send SQL statement to database.</i>
---------------	--

Description

Send SQL statement to database.

Usage

```
sendStatement(db, statement, ...)
```

Arguments

db	rocker object
statement	SQL statement (UPDATE, DELETE, INSERT INTO, ...)
...	Optional, additional suitable parameters passed to DBI::dbSendStatement()

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::sendStatement(db, "DELETE FROM mtcars WHERE gear = 3;")
rocker::clearResult(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

setupDriver	<i>Setup database driver and define connection parameters.</i>
-------------	--

Description

Setup database driver and define connection parameters.

Usage

```
setupDriver(db, drv, protect = c("password", "user"), ...)
```

Arguments

db	rocker object
drv	Driver object from suitable package e.g. RPostgres::Postgres() , RMariaDB::MariaDB() and RSQLite::SQLite()
protect	Parameters to be hidden
...	Suitable parameters passed to DBI::dbConnect() e.g. host, port, dbname, user and password

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupDriver(
  db,
  drv = RSQLite::SQLite(),
  dbname = ":memory:"
)
rocker::unloadDriver(db)
```

setupMariaDB	<i>Setup database driver and define connection parameters for MariaDB using RMariaDB package. Wrapper for <code>setupDriver()</code> function.</i>
--------------	--

Description

Setup database driver and define connection parameters for MariaDB using [RMariaDB](#) package. Wrapper for `setupDriver()` function.

Usage

```
setupMariaDB(
  db,
  host = "127.0.0.1",
  port = "3306",
  dbname = "mydb",
  user = "root",
  password = "password",
  protect = c("password", "user"),
  ...
)
```

Arguments

db	rocker object
host	Host name or IP number
port	Port number
dbname	Database name
user	User name
password	Password
protect	Parameters to be hidden
...	Optional, additional suitable parameters passed to <code>DBI::dbConnect()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupMariaDB(
  db,
  host = "127.0.0.1", port = "3306", dbname = "mydb",
  user = "root", password = "password"
)
rocker::unloadDriver(db)
```

setupPostgreSQL	<i>Setup database driver and define connection parameters for PostgreSQL using RPostgres package. Wrapper for setupDriver() function.</i>
-----------------	---

Description

Setup database driver and define connection parameters for PostgreSQL using [RPostgres](#) package. Wrapper for setupDriver() function.

Usage

```
setupPostgreSQL(
  db,
  host = "127.0.0.1",
  port = "5432",
  dbname = "mydb",
  user = "postgres",
  password = "password",
  protect = c("password", "user"),
  ...
)
```

Arguments

db	rocker object
host	Host name or IP number
port	Port number
dbname	Database name
user	User name
password	Password
protect	Parameters to be hidden
...	Optional, additional suitable parameters passed to DBI::dbConnect()

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupPostgreSQL(
  db,
  host = "127.0.0.1", port = "5432", dbname = "mydb",
  user = "postgres", password = "password"
)
rocker::unloadDriver(db)
```

setupSQLite	<i>Setup database driver and define connection parameters for SQLite using RSQLite package. Wrapper for setupDriver() function.</i>
-------------	---

Description

Setup database driver and define connection parameters for SQLite using [RSQLite](#) package. Wrapper for [setupDriver\(\)](#) function.

Usage

```
setupSQLite(db, dbname = ":memory:", protect = c("password", "user"), ...)
```

Arguments

db	rocker object
dbname	Database name
protect	Parameters to be hidden
...	Optional, additional suitable parameters passed to DBI::dbConnect()

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(
  db,
  dbname = ":memory:"
)
rocker::unloadDriver(db)
```

unloadDriver

Reset database driver and connection parameters.

Description

Reset database driver and connection parameters.

Usage

```
unloadDriver(db, ...)
```

Arguments

db	rocker object
...	Optional, suitable parameters passed to <code>DBI::dbUnloadDriver()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [validateCon\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::unloadDriver(db)
```

validateCon	<i>Check if an earlier opened connection is still open.</i>
-------------	---

Description

Check if an earlier opened connection is still open.

Usage

```
validateCon(db, statement = NULL, onLostNull = FALSE, ...)
```

Arguments

db	rocker object
statement	Optional SQL statement. If not set default validateQuery will be used.
onLostNull	TRUE or FALSE. If connection lost, set .con to NULL
...	Not used yet

Value

TRUE or FALSE

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [writeTable\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::validateCon(db)
rocker::disconnect(db)
rocker::unloadDriver(db)
```

writeTable	<i>Write data to table.</i>
------------	-----------------------------

Description

Write data to table.

Usage

```
writeTable(db, name, value, ...)
```

Arguments

db	rocker object
name	Table name
value	Values data.frame
...	Optional, additional suitable parameters passed to <code>DBI::dbWriteTable()</code>

Value

Invisible self

See Also

Other rocker-S3-functions: [appendTable\(\)](#), [begin\(\)](#), [canConnect\(\)](#), [clearResult\(\)](#), [columnInfo\(\)](#), [commit\(\)](#), [connect\(\)](#), [createTable\(\)](#), [disconnect\(\)](#), [execute\(\)](#), [existsTable\(\)](#), [fetch\(\)](#), [getInfoCon\(\)](#), [getInfoDrv\(\)](#), [getInfoRes\(\)](#), [getQuery\(\)](#), [getRowCount\(\)](#), [getRowsAffected\(\)](#), [getStatement\(\)](#), [hasCompleted\(\)](#), [isValidCon\(\)](#), [isValidDrv\(\)](#), [isValidRes\(\)](#), [listFields\(\)](#), [listObjects\(\)](#), [listTables\(\)](#), [readTable\(\)](#), [removeTable\(\)](#), [rocker-README](#), [rocker-S3-functions](#), [rocker-package](#), [rollback\(\)](#), [sendQuery\(\)](#), [sendStatement\(\)](#), [setupDriver\(\)](#), [setupMariaDB\(\)](#), [setupPostgreSQL\(\)](#), [setupSQLite\(\)](#), [unloadDriver\(\)](#), [validateCon\(\)](#)

Examples

```
db <- rocker::newDB()
rocker::setupSQLite(db)
rocker::connect(db)
rocker::writeTable(db, "mtcars", mtcars)
rocker::disconnect(db)
rocker::unloadDriver(db)
```


Index

* rocker-S3-functions

- appendTable, 2
- begin, 3
- canConnect, 4
- clearResult, 5
- columnInfo, 6
- commit, 7
- connect, 8
- createTable, 9
- disconnect, 10
- execute, 11
- existsTable, 12
- fetch, 13
- getInfoCon, 14
- getInfoDrv, 15
- getInfoRes, 16
- getQuery, 17
- getRowCount, 18
- getRowsAffected, 19
- getStatement, 20
- hasCompleted, 21
- isValidCon, 22
- isValidDrv, 23
- isValidRes, 24
- listFields, 25
- listObjects, 26
- listTables, 27
- readTable, 28
- removeTable, 29
- rocker-README, 56
- rocker-S3-functions, 78
- rollback, 79
- sendQuery, 80
- sendStatement, 81
- setupDriver, 82
- setupMariaDB, 83
- setupPostgreSQL, 84
- setupSQLite, 85
- unloadDriver, 86

- validateCon, 87

- writeTable, 88

* rocker

- newDB, 28
- rocker-R6-class, 30
- rocker-README, 56
- rocker-S3-functions, 78

- appendTable, 2, 4–27, 29, 30, 78–83, 85–88

- begin, 3, 3, 5–27, 29, 30, 78–83, 85–88

- canConnect, 3, 4, 4, 5–27, 29, 30, 78–83, 85–88

- clearResult, 3–5, 5, 6–27, 29, 30, 78–83, 85–88

- columnInfo, 3–5, 6, 7–27, 29, 30, 78–83, 85–88

- commit, 3–6, 7, 8–27, 29, 30, 78–83, 85–88

- connect, 3–7, 8, 9–27, 29, 30, 78–83, 85–88

- createTable, 3–8, 9, 10–27, 29, 30, 78–83, 85–88

- DBI, 28, 30, 78

- DBI::dbAppendTable(), 3, 44

- DBI::dbBegin(), 4, 40

- DBI::dbCanConnect(), 4, 34

- DBI::dbClearResult(), 5, 39

- DBI::dbColumnInfo(), 6, 38

- DBI::dbCommit(), 7, 40

- DBI::dbConnect(), 8, 32–35, 82–85

- DBI::dbCreateTable(), 9, 43

- DBI::dbDisconnect(), 10, 35

- DBI::dbExistsTable(), 12, 45

- DBI::dbFetch(), 13, 37

- DBI::dbGetInfo(), 14–16, 41

- DBI::dbGetRowCount(), 18, 38

- DBI::dbGetRowsAffected(), 19, 38

- DBI::dbGetStatement(), 20, 39

- DBI::dbHasCompleted(), 21, 37

- DBI::DBIConnection-class, 30
- DBI::DBIDriver-class, 30
- DBI::DBIResult-class, 30
- DBI::dbIsValid(), 22–24, 42, 43
- DBI::dbListFields(), 25, 46
- DBI::dbListObjects(), 26, 46
- DBI::dbListTables(), 27, 46
- DBI::dbReadTable(), 28, 44
- DBI::dbRemoveTable(), 29, 45
- DBI::dbRollback(), 40, 79
- DBI::dbSendQuery(), 17, 35, 36, 80
- DBI::dbSendStatement(), 11, 36, 81
- DBI::dbUnloadDriver(), 34, 86
- DBI::dbWriteTable(), 44, 88
- disconnect, 3–9, 10, 11–27, 29, 30, 78–83, 85–88
- execute, 3–10, 11, 12–27, 29, 30, 78–83, 85–88
- existsTable, 3–11, 12, 13–27, 29, 30, 78–83, 85–88
- fetch, 3–12, 13, 14–27, 29, 30, 78–83, 85–88
- getInfoCon, 3–13, 14, 15–27, 29, 30, 78–83, 85–88
- getInfoDrv, 3–14, 15, 16–27, 29, 30, 78–83, 85–88
- getInfoRes, 3–15, 16, 17–27, 29, 30, 78–83, 85–88
- getQuery, 3–16, 17, 18–27, 29, 30, 78–83, 85–88
- getRowCount, 3–17, 18, 19–27, 29, 30, 78–83, 85–88
- getRowsAffected, 3–18, 19, 20–27, 29, 30, 78–83, 85–88
- getStatement, 3–19, 20, 21–27, 29, 30, 78–83, 85–88
- hasCompleted, 3–20, 21, 22–27, 29, 30, 78–83, 85–88
- isValidCon, 3–21, 22, 23–27, 29, 30, 78–83, 85–88
- isValidDrv, 3–22, 23, 24–27, 29, 30, 78–83, 85–88
- isValidRes, 3–23, 24, 25–27, 29, 30, 78–83, 85–88
- listFields, 3–24, 25, 26, 27, 29, 30, 78–83, 85–88
- listObjects, 3–25, 26, 27, 29, 30, 78–83, 85–88
- listTables, 3–26, 27, 29, 30, 78–83, 85–88
- newDB, 28, 46, 78
- R6, 28, 30, 78
- R6Class, 30
- readTable, 3–27, 28, 30, 78–83, 85–88
- removeTable, 3–27, 29, 29, 78–83, 85–88
- RMariaDB, 33, 83
- RMariaDB::MariaDB(), 32, 82
- rocker, 28
- rocker (rocker-R6-class), 30
- rocker-R6-class, 30
- rocker-README, 56
- rocker-S3-functions, 78
- rollback, 3–27, 29, 30, 78, 79, 80–83, 85–88
- RPostgres, 32, 84
- RPostgres::Postgres(), 32, 82
- RSQLite, 34, 85
- RSQLite::SQLite(), 32, 82
- sendQuery, 3–27, 29, 30, 78, 79, 80, 81–83, 85–88
- sendStatement, 3–27, 29, 30, 78–80, 81, 82, 83, 85–88
- setupDriver, 3–27, 29, 30, 78–81, 82, 83, 85–88
- setupMariaDB, 3–27, 29, 30, 78–82, 83, 85–88
- setupPostgreSQL, 3–27, 29, 30, 78–83, 84, 86–88
- setupSQLite, 3–27, 29, 30, 78–83, 85, 85, 86–88
- unloadDriver, 3–27, 29, 30, 78–83, 85, 86, 86, 87, 88
- validateCon, 3–27, 29, 30, 78–83, 85, 86, 87, 88
- writeTable, 3–27, 29, 30, 78–83, 85–87, 88